introduction

The automatic door opener is designed and tested to offer safe service provided it is installed and operated in strict accordance with safety warnings outlined in the installation manual.

Overhead door openers power sectional and other overhead doors, such as tilt doors. Our openers use advanced DC motors to ensure smooth and reliable operation. We offer 6 residential openers so you can perfectly match the opener to your requirements. The Smart Phone Control Kit is an optional accessory on many of our Sectional Door Openers.

Rolling Door openers are made specifically to power this popular garage door type. Rolling doors are smooth and quiet to operate when combined with a quality automatic opener and do not require mounting to the ceiling. We use advanced DC motors for our rolling door openers to ensure smooth and reliable operation.

The Axess Pro Series 3000 range provide an innovative suite of features for the demanding world of industrial shutter automation. With a selection of input and output power variations and a scalable suite of control and safety options, this combination of strength and smarts is a evolutionary step forward.

Gate openers are available for sliding or swing gates. They are perfect for the majority of residential gates and opeerate gates from 500 - 800kg (6 - 8m) for sliding gates and 250kg (4m leaf) for swing gates.

Individual product datasheets are available online at bnd.com.au/automation-remotes

spare parts

Each opener has a detailed spare parts list, which lists the parts available to purchase by product, the part number and an exploded parts diagram.

To view the current spare parts list please consult your B&D representative.

pricing

For the full list of products available for sale please refer to the latest B&D pricelist.

Key Accessories				
Туре	Order #	Description		
Battery Backup	62737	Battery Back Up - Gen2		
Safahi Pagma	62876	Wireless Safety Beams		
Safety Beams	62626	2-Wire Safety Beams		
Solar	62855	SmartSolar™ Kit - Gen2		
	14835	Smart Hub and Transceiver		
Smart Phone Control Kit	MC0008	Smart Hub		
	MC0009	Transceiver		

Locks & Key Switches					
Description					
Key Switch (Barrel Type) #801					
Key Switch (Barrel Type) Keyed Randomly (without imprint)					
6' Keyed (J-30) Outside Disconnect For Sectional & Tilt					
6' Keyed (Random) Outside Disconnect					
Electric & Manual Override Switch For Roll Up Doors					
Electric Pulse Lock 12V 15VA 50Hz power supply required - Includes fixings					
Neoslider Keys Manual Release					
Spare Key GDO8V3 SGO1V4					



opener range

Following tables list the opener range for both residential and industrial openers

bad	477			0	0
RESIDENTIAL					
Model Name	PanelPro SDO-4V1	Secure SDO-6	Smart SDO-7	Roll-A-Pro RDO-1V3	Power Drive RDO-1V4
Part Number#	62869	86246	86247	62886	62887
Type of door	Sectional	Sectional	Sectional	Rolling	Rolling
Peak Short Term Pulling Force	650N	1100N	1100N	600N	600N
Maximum Door Weight	110kg	236kg	236kg	110kg	110kg
Rated Door Area	13.5m²	18.0m²	18.0m²	16.5m²	16.5m²
Rail	Steel / Alum.	Steel / Alum.	Steel / Alum.		
Drive	Chain / Belt	^Lockable	^Lockable		
Speed (mm/sec)	140	115/150/180	115/150/180	120	120
Dimensions W x H x D (mm)	216 x 228 x154	225 x 353 x150	225 x 353 x150	320 x388 x200	320 x388 x200
Side Room Req.				40mm	40mm
Rail Headroom	25mm	30mm	30mm		
Minimum Headroom	57mm	57mm	57mm		
Soft Start / Soft Stop	•	•	•	•	•
Lighting System	Festoon	60W LED	60W LED	LED	LED
Transmitter storage capacity	8	64	64	8	64
Warranty	5 year / 10,000 cycles	*7 year / 20,000 cycles	*7 year / 20,000 cycles	5 year / 10,000 cycles	7 year / 20,000 cycles
Accessories					
4 Button Transmitters	x 3	x 2	x 2	x 3	x 2
Wall Transmitter		x 1	x 1		x 1
Safety Beams (Optional)	•	•	•	•	•
Battery Back Up (Optional)	•		•		•
Smart Phone Control (Optional)	•	•	Standard		•
Wireless Auto Lock (Optional)	•	٠	•		
SmartSolar™ (Optional)				•	•
INDUSTRIAL					
Model Name	Hiro GDO-12	Toro GDO-10V3	Axess Pro 1505	Axess Pro 3100	Axess Pro 3300
Part Number#	60195	61480	62670	62618	62617 / 62619
Туре	Roller	Roller	Overhead	Shutter / Wind Lock	Shutter
Maximum door / gate area	22.0m ² */ 28.0m ²	22.0m ² */ 28.0m ²	25m²	36m² / 28m²	36m² (1HP) 50m² (1.5HP)
Motor Power	1400N	1000N	0.5 HP	1HP	1 or 1.5HP
Warranty	2 year / 10,000 cycles	2 year / 5,000 cycles	5 year / 10,000 cycles	5 year / 10,000 cycles	2 years
Accessories					
4 Button Transmitters	x 2	x 2	x 2	x 2	x 2
Manual / Logic Console		хl	x 1	x 1	x 1
Safety Beams (Optional)	•	•	included	•	•
Smart Phone Control (Optional)	•				

aut^omatic TECHNOLOGY **RESIDENTIAL**













Model Name Ero GDO-11 Tempo ATS-2 Syncro GDO-6V Part Number# 62978 86232 86233 62715 Type of door Sectional Sectional Rolling Peak Short Term Pulling Force 650N 1100N 1100N 600N Maximum Door Weight 110kg 200kg 236kg 110kg Rated Door Area 13.5m² 18.0m² 18.0m² 16.5m² Rail Steel / Alum. Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm Soft Start / Soft Stop • • •	GDO-6V4 62717 Rolling	ShedMaster GDO-8V3 62095
Type of door Sectional Sectional Sectional Rolling Peak Short Term Pulling Force 650N 1100N 1100N 600N Maximum Door Weight 110kg 200kg 236kg 110kg Rated Door Area 13.5m² 18.0m² 18.0m² 16.5m² Rail Steel / Alum. Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm	Rolling	62095
Peak Short Term Pulling Force 650N 1100N 1100N 600N Maximum Door Weight 110kg 200kg 236kg 110kg Rated Door Area 13.5m² 18.0m² 18.0m² 16.5m² Rail Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm		
Maximum Door Weight 110kg 200kg 236kg 110kg Rated Door Area 13.5m² 18.0m² 18.0m² 16.5m² Rail Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm		Rolling
Rated Door Area 13.5m² 18.0m² 18.0m² 16.5m² Rail Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm	600N	550N
Rail Steel / Alum. Steel / Alum. Steel / Alum. Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm	110kg	100kg
Drive Chain / Belt Chain / Belt Chain / Belt Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm	16.5m ²	16.5m²
Speed (mm/sec) 140 115/150/180 115/150/180 120 Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm		
Dimensions W x H x D (mm) 216 x 228 x154 225 x 353 x150 225 x 353 x150 291 x 383 x Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm 57mm		
Side Room Req. 40mm Rail Headroom 25mm 30mm 30mm Minimum Headroom 57mm 57mm	120	100
Rail Headroom25mm30mm30mmMinimum Headroom57mm57mm57mm	183 291 x 383 x183	309 x 250 x187
Minimum Headroom 57mm 57mm 57mm	40mm	40mm
Soft Start / Soft Stop · · · ·		
	•	
Lighting System Festoon 60W LED 60W LED LED	LED	Optional
Transmitter storage capacity 8 64 64 8	64	8
Warranty 5 year / 7 year / 7 year / 5 year / 10,000 cycles 20,000 cycles 20,000 cycles 10,000 cycles		2 year / 5,000 cycles
Accessories		
4 Button Transmitters x 3 x 2 x 2 x 3	x 2	x 2
Wall Transmitter x 1 x 1	x 1	
Safety Beams (Optional) • • • •	•	•
Battery Back Up (Optional) • • •	•	
Smart Phone Control (Optional) • Standard	•	
Wireless Auto Lock (Optional)		
SmartSolar™ (Optional) • •		

GATES			
Model Name	NeoSlider 500	NeoSlider 800	Elite + DCB-05 SGO-1V4
Part Number#	60196	60198	62670
Type of gate	Slider	Slider	Swing
Peak Short Term Pulling Force	280N	700N	200N
Maximum Gate Weight	500kg	800kg	250kg
Rated Gate Area	6m	8m	4m leaf
Transmitter storage capacity	30	30	30
Warranty	2 year / 5,000 cycles	2 year / 5,000 cycles	2 year / 5,000 cycles
Accessories			
4 Button Transmitters	x 2	x 2	x 2
Battery Backup (Optional)	•	•	•
Safety Beams (Optional)	•	•	•
Smart Phone Control (Optional)	٠	•	With DCB-05



*Terms & Conditions apply, See <u>www.bnd.com.au</u> for details

PROTECTED BY







transmitter compatibility

Below two tables list the transmitter accessories compatibily with the current and obselete product range.

CURRENT PRODUCT RANGE COMPATIBILITY		SMART PHONE	TB-6	TB-6	TB-5V2	WTB-6	KPX-7V2
		14835	62872	62871	62874	62873	62875
	PANELPRO SDO-1V4	1	1	1	1	1	1
SECTIONAL DOOR OPENERS	CAD SMART SDO-7	1	1	1		1	1
DOOK OF ENERS	CAD SECURE SD0-6	1	1	1		1	1
	CAD POWERDRIVE	1	1	1		1	1
ROLLING DOOR OPENERS	ROLL-A-PRO RDO-1V3	1	1	1	1	1	1
OI LINERS	HIRO™GDO-12	•	1	1	1	1	•

Standard 🗸	Optional 🗸			*		De De	•	•1
OBSOLETE PRODUCT RANGE COMPATIBILITY		TB-6	TB-6	TB-5V2	TB-5	PTX-4 B&D	WTB-6	KPX-7V2
		62872	62871	62874		59120	62873	62875
	CAD P DIAMOND				1	1		
	CAD ADVANCE SDO-2V2	1	1				1	1
SECTIONAL DOOR OPENERS	CAD P DIAMOND SDO-2V2	1	1	1				
DOOK OF LIVERS	CAD PRODIGY SDO-2V3	1	1				1	1
	CAD S SDO-3V2	1	1				1	1
ROLLING DOOR	CAD PD RDO-1V3			1				1
OPENERS	DIAMOND PD RDO-1				1	1		1
REPLACEMENT			STILL AVAILABLE	STILL AVAILABLE	TB-5V2 (************************************	STILL AVAILABLE	STILL AVAILABLE	STILL AVAILABLE

safety beam compatibility

Below table list the safety beam compatibily with the current product range.

PRODUCT		V	WIRELESS 2-WIRE		IRE	3-WIRE	NO. OF SB INPUTS	
	PART #	86920	86802	62738	86925	62626	62627	
GARAGE DO	OR OPENERS					,		
CAD SMART, O	CAD SECURE	•			•			x 2
PANELPRO				•		•		x 2
CAD POWERD	RIVE			•		•		x 2
ROLL-A-PRO				•		•		x 2
SHEDMASTER	₹						•	x 1
COMMERCIA	L OPENERS	,		,		,		
GDO-12 HIRO			•			•		х 3
GDO-10V3L2 T	TORO			•		•		х 3
INDUSTRIAL	. OPENERS							
AXESS 1505	L2 CONSOLE			•		•		х 3
AXESS 3000	L1 CONSOLE			•		•	•	x 1
PRO SERIES	L2 CONSOLE			•		•		х 3

